

TEMP°ALERT®



MTA-1

Model Number: MTA-1
Part Number: M-001-0098

Applications:

IT Server rooms
Residential/vacation homes
Office settings

Need to know:

Power Requirements: No power required to operate
Low Limit Adjust Range: 30° to 90° F (-1° to 32.2° C) Non-condensing environment.
High Limit Adjust Range: 40° to 100° F (4° to 37.7° C) Non-condensing environment.
Minimum Temp Span: 10° Recommended distance between high and low set points.
Temp Accuracy: $\pm 3^{\circ}$ F ($\pm 1.7^{\circ}$ C)
Temp Response Time: TC = 14 minutes
Outputs: Gold plated N.O. dry contacts. Not for high voltage use.
Contact Output Rating: 12VDC @ 50mA
Weight: 6 oz (0.17 kg)
Dimensions: 4.5 x 3.25 x 1" (11.4 x 8.3 x 2.5 cm)
Mounting: Surface mount

Not for use inside coolers/freezers - use EnviroAlert with hard wired probe.
Connects to any hard wire or wireless alarm system.
Separate output for high and low alarm signals.
Sleek, low-profile styling.
Normally open (N.O.)



WINLAND
ELECTRONICS, INC.

Mankato, MN
www.winland.com
800-635-4269



010312