

TEMP°ALERT®

PROTECT PROPERTY FROM THE ADVERSE EFFECTS OF TEMPERATURE EXTREMES



TA-2HL Temperature Monitor

- Monitors -30 to +130° F (-34 to +54° C)
- Adjustable high and low alarm set points
- Requires no power to operate
- Connects to any hardwire or wireless alarm system
- Separate output for high and low alarms signals
- 15' signal cable exits rear of unit for clean appearance
- **Not for use in freezer or cooler monitoring, instead use an EnviroAlert® with a remote probe**

SPECIFICATIONS

TA-2HL TEMP°ALERT®

SPECIFICATION	VALUE
Low Limit Adjust Range	-30 to +120° F (-34 to +49° C)
High Limit Adjust Range	-20 to +130° F (-29 to +54° C)
Minimum Span (Rec. dist. between high and low set pts.)	10° F (5.6° C)
Temp Accuracy	±3° F (±1.7° C)
Temp Response Time	TC= 14 minutes
Temp Sensing Element	Bimetallic coil
Outputs (Not for high voltage use)	Gold plated N/O Dry Contacts
Contact Output Rating	12VDC @ 50mA
Control Box Material	ABS
Weight	6 ounces (170 g)
Dimensions	6.25" x 3.75" x 1" (15.9 cm x 9.5 cm x 2.5 cm)
Mounting	Key slot



1950 Excel Drive
Mankato, MN 56001
1-800-635-4269
In MN: 507-625-7231
FAX: 507-387-2488
www.winlandsecurity.com

