

TEMP°ALERT®



TA-2HL

Model Number: TA-2HL
Part Number: M-001-0100

Applications:

Livestock buildings
Warehouses
Basements/Garages/Attics
Industrial settings

Need to know:

Power Requirements: No power required to operate
Low Limit Adjust Range: -30° to 120° F (-34° to 49° C) Non-condensing environment.
High Limit Adjust Range: -20° to 130° F (-29° to 54° C) Non-condensing environment.
Minimum Temp Span: 10° Recommended distance between high and low set points.
Temp Accuracy: $\pm 3^{\circ}$ F ($\pm 1.7^{\circ}$ C)
Temp Response Time: TC = 14 minutes
Outputs: Gold plated N.O. dry contacts. Not for high voltage use.
Contact Output Rating: 12VDC @ 50mA
Weight: .75 lb (0.34 kg)
Dimensions: 6.25 x 3.75 x 1" (15.9 x 9.5 x 2.5 cm)
Mounting: Key slot

Not for use inside coolers/freezers - use EnviroAlert with hard wired probe.
Connects to any hard wire or wireless alarm system.
Separate output for high and low alarm signals.
15' (4.57 m) signal cable exits rear of unit for clean appearance.
Retro styling.
Normally open (N.O.)



WINLAND
ELECTRONICS, INC.

Mankato, MN
www.winland.com
800-635-4269



010312