

# TEMP°ALERT®

PROTECT PROPERTY FROM THE ADVERSE EFFECTS OF TEMPERATURE EXTREMES



## TA-1 (PN 1014) Temperature Monitor

- Monitors -30 to 130° F (-34 to 54° C)
- Adjustable high and low alarm set points
- Requires no power to operate
- Connects to any hardwire or wireless alarm system
- **Not for use in freezer or cooler monitoring, instead use an EnviroAlert® with a remote probe**



**WINLAND**  
ELECTRONICS, INC.

# SPECIFICATIONS

## TA-1 TEMP°ALERT®

SPECIFICATION	VALUE
Low Limit Adjust Range	-30 to 120° F (-34 to 49° C)
High Limit Adjust Range	-20 to 130° F (-29 to 54° C)
Minimum Span (Rec. dist. between high and low set pts.)	10° F (5.6° C)
Temp Accuracy	±3° F (±1.7° C)
Temp Response Time	TC= 14 minutes
Temp Sensing Element	Bimetallic coil
Outputs (Not for high voltage use)	Gold plated N/O Dry Contacts
Contact Output Rating	12VDC @ 50mA
Control Box Material	ABS
Weight	6 ounces (170 g)
Dimensions	6.25" x 3.75" x 1" (15.9 cm x 9.5 cm x 2.5 cm)
Mounting	1/4" slotted

Unavailable in the European Union



**WINLAND**  
ELECTRONICS, INC.

1950 Excel Drive  
Mankato, MN 56001

1-800-635-4269  
In MN: 507-625-7231  
FAX: 507-387-2488

[www.winland.com](http://www.winland.com)

©2006 Winland Electronics Inc.  
D-011-0027 Rev. C