

ENVIROALERT®

Accessory for:
EnviroAlert EA800-ip

Wireless Temperature Accessory for EnviroAlert EA800-ip

- Transmission distance of 45' to 100' indoor (results may vary)
- Set temperature high/low set points on EnviroAlert console.
- Do **NOT** put EA-WMFS in freezer/cooler. Use wired sensor.
- Max probe cable run: 1,000' (305 m) [18 - 22 twisted pair]



EA-WMFS
Shown with TEMP-H-S sensor
(sensor sold separately)

Specifications

Sensing Range	Remote sensor dependent - requires remote sensor for operation
Power Requirements	2 - AA Alkaline Batteries or 12 VDC @ <=100mA
Battery Life	Alkaline up to 1 year (not included)
Unit Operating Range	32° to 122° F (0° to 50° C) Non-condensing environment
Frequency	2.405 GHz - 2.480 GHz, 16 channels. See owner's manual for more information
Transmission Distance	45' to 100' indoor (results may vary)
Weight	0.25 lb (0.11 kg)
Dimensions	3.67 x 2.65 x 1.17" (9.3 x 6.7 x 2.9 cm)
Mounting	Surface Mount

Requires Sensor for operation

Accessory sensors:

Detection

Temp Ultra Low (White) Stainless Steel
Temp Low (Blue) Stainless Steel
Temp Low (Blue) Waterproof
Temp High (Red) Stainless Steel
Temp High (Red) Waterproof
Water Surface Sensor (supervised)
PS-110 Power Out Alert

Model

TEMP-UL-S
TEMP-L-S
TEMP-L-W
TEMP-H-S
TEMP-H-W
W-S-S
PS-110

Number Range

-112° to 32° F (-80 to 0°)
-58° to 158° F (-50 to 70° C)
-58° to 158° F (-50 to 70° C)
32° to 302° F (0 to 150° C)
32° to 221° F (0 to 105° C)

N.O./N.C. devices



Visit www.winland.com, call 800.635.4269 or email techsupport@winland.com to learn more.

424 North Riverfront Drive, Suite 200 • Mankato, MN • 56001 • 800.635.4269 • www.winland.com