



Features	EA800-ip	EAPro®-Gateway
Wire Inputs	4	4
RF Inputs	8 Max	30 Max
Relay Outputs	9	5
Relay Power Output @ 1 Amp.	Yes (9 relays)	Yes (4 Relays)
Relay Power Output @ 3 Amp.	No	Yes (1 Relay)
Latching Relay ¹	No	Yes (optional selectable)
Non-Latching Relay ²	Yes	Yes (optional selectable)
Remote Management	Yes	Yes
Standalone ³	Yes	Yes
CRF 21 Part 11 Guidelines ⁴	No	Yes
Individual Relay ⁵ High/Low Option	No	Yes
Stackable Relay ⁶ Setpoints	Yes, for entire sensor	Yes, for each setpoint
Optional Relay Trip ⁷	Requires a relay (AUX)	Yes
Event Only Relay ⁸	No	Pending / Optional
Independent High/ Low ⁹ Programming Per Sensor	Yes	Yes
Independent Warning Set ¹⁰ Points Programming Per Sensor	No	Yes

Visit www.winland.com, call 800.635.4269 or email techsupport@winland.com to learn more.



Features	EA800-ip	EAPro®-Gateway
Touchscreen	No	Yes
Remote Configuration ¹¹ Storage	No	Yes
Wi-Fi ¹²	No	Yes
PoE	No	Yes
Pausing ¹³	Device Level	Sensor Level
Datalogging	Device Level	Sensor Level
Min/Max Sensor Reading	No	Yes
VFC Guideline ¹⁴	No	Yes - limited distance
Power Requirement	11~26V @ 500mA	11~26V @ 1A
Clock Battery	Yes	Yes
Internal Battery UPS	No	Yes
User Logging (Local) ¹⁵	No	Yes
LED Indication	No	Yes (Optional Selectable)
Local Buzzer	Yes	Yes (Optional Selectable)
Energized / De-Energize ¹⁶ Relay	Yes (Configurable)	Yes (Configurable)
Relay Test ¹⁷	No	Yes

Visit www.winland.com, call 800.635.4269 or email techsupport@winland.com to learn more.

- 1 - Latching Relay:
Relays stays in alarm condition until manual clear.
- 2 - Non-Latching Relay:
Relay auto-clears once zone is back within set range.
- 3 - Standalone:
No network requirement / can be used without **INSIGHT**.
- 4 - CRF 21 Part 11 Guidelines:
This device is NOT CFR 21 Part 11 Certified at this time. Auditing has been enhanced.
- 5 - Individual Relay High / Low Option:
One output for either High Alarm or Low Alarm.
- 6 - Stackable Relay Setpoints:
Allows for merged output of multiple zones.
- 7 - Optional Relay Trip:
Ability to have a relay disabled per sensor.
- 8 - Event Only Relay:
Relay to trigger offline, loss of sensor RF, customizable.
- 9 - Independent High / Low Programming Per Sensor:
Program a sensor to only send an alarm for either a High Alarm or Low Alarm.
- 10 - Independent Warning Set Points Programming Per Sensor:
Ability to program an additional warning set point for a sensor to be alerted before conditions get critical.
- 11 - Remote Configuration Storage:
Allows **INSIGHT** to store your configuration file for retrieval at a later time.
- 12 - Wi-Fi:
2.4Ghz only.
- 13 - Pausing:
Pause monitoring for maintenance.
- 14 - VFC Guideline:
Vaccine For Children is a guideline that vaccines often have to follow.
- 15 - User Logging (Local):
Independent access levels for user accounts to control permissions and auditing.
- 16 - Energized / De-Energize Relay:
Monitor relay based on loss of power as well as sensor.
- 17 - Relay Test:
Ability to test relay for alarm panel validation.

Visit www.winland.com, call 800.635.4269 or email techsupport@winland.com to learn more.

424 North Riverfront Drive, Suite 200 • Mankato, MN • 56001 • 800.635.4269 • www.winland.com