



## WATERBUG®

### Accessory Sensors

#### Detection

- Water Sensor Surface (unsupervised)
- Water Sensor Under Carpet (Unsupervised)

#### Model Number


- W-S-U
- W-UC-U





### Battery Operated Water Detection offers wide area coverage

- 9V battery powered (battery not included).
- Integrated buzzer alarms on water presence and low battery.
- Includes one standard surface sensor unsupervised (W-S-U).
- Connect up to 6 sensors wired in parallel up to 100' (30.5 m) using 18-22 AWG twisted pair.
- Open collector output.
- Will not alarm due to condensation or humidity.
- Designed to detect nonflammable conductive liquids (distilled water cannot be detected).

(Optional) MOUNTING  
Drill in this innermost center circle only.



**Four Probe Contacts**  
Mount the probe to ensure these four stainless steel contacts are against the surface to be monitored.



### Specifications

Current Draw	9VDC via alkaline battery @ 40 (Micro Amps)
Operating Range	Console and sensor 32 to 140°F (0 to 60°C)
Output	Open Collector Transistor Output (N.O. Circuit Only) Max to trip line: 30VDC; Max to collector: 25mA
Sensor Included	1 Standard surface sensor unsupervised (W-S-U)
Max Distance Sensor/Console	1-2 sensors; max 200' (61 m) 3-6 sensors; max 100' (30.5 m) per sensor
Console Dimensions	5 x 2.44 x 1.25" (12.7 x 6.2 x 3.18 cm)
Sensor Dimensions	3.0 x 2.0 x .88" (5.1 x 7.6 x 2.2 cm)
Weight	14 oz. (0.40 kg)
Mounting	Key Slot



Visit [www.winland.com](http://www.winland.com), call 800.635.4269 or email [techsupport@winland.com](mailto:techsupport@winland.com) to learn more.

424 North Riverfront Drive, Suite 200 • Mankato, MN • 56001 • 800.635.4269 • [www.winland.com](http://www.winland.com)